

**34566-384**

## FUNKTIONER

Aluminum extrusion, anodized finish, conductive contact surface, with HP markings



|                                                                                                                                         |                                                                                   | $\sigma_{\text{th}}^{\text{th}}$ can be combined, $\sigma_{\text{th}}^{\text{th}}$ combination not recommended |                                                                                   |                                                                                   |                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| <br>Extruded T<br>$\sigma_{\text{th}}^{\text{th}} = 1$ |  | -                                                                                                              | +                                                                                 | +                                                                                 | +                                                                                 |
|                                                                                                                                         |  | +                                                                                                              | extruded T-flange and<br>extruded T-flange<br>not possible                        | +                                                                                 | +                                                                                 |
| <br>Extruded T<br>$\sigma_{\text{th}}^{\text{th}} = 1$ |  | extruded T-flange<br>not possible                                                                              | extruded T-flange<br>not possible                                                 | -                                                                                 | -                                                                                 |
|                                                                                                                                         |  | +                                                                                                              | +                                                                                 | -                                                                                 | -                                                                                 |
| Perforated rail<br>Side panel                                                                                                           |  |                               |  |  |  |
|                                                                                                                                         | Light $\neq 1$                                                                    | Flange $\neq 1$                                                                                                | Heavy $\neq 10$                                                                   | Rugged $\neq 8$                                                                   |                                                                                   |

Green: floor system

## PRODUKTEGENSKABER

Gross Weight: 0.259kg

nVent.com/SCHROFF | 1

## ADVARSEL

---

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på [www.nvent.com](http://www.nvent.com) og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

### North America

All locations  
+1.763.422.2661  
Chat with us:  
[nvent.com/schroff](http://nvent.com/schroff)

### Europe

Straubenhardt, Germany  
+49.7082.794.0  
Betschdorf, France  
+33.3.88.90.64.90  
Warsaw, Poland  
+48.22.209.98.35  
Assago, Italy  
+39.02.932.7141  
Chat with us:  
[nvent.com/schroff](http://nvent.com/schroff)

### Asia

Shanghai, China  
+86.21.2412.6943  
Qingdao, China  
+86.532.8771.6101  
Singapore  
+65.6768.5800  
Shin-Yokohama, Japan  
+81.45.476.0271  
Chat with us:  
[nvent.com/schroff](http://nvent.com/schroff)

### Middle East & India

Dubai, United Arab Emirates  
+971.4.378.1700  
Bangalore, India  
+91.80.6715.2001  
Istanbul, Turkey  
+90.216.250.7374  
Chat with us:  
[nvent.com/schroff](http://nvent.com/schroff)

