



Combinations of horizontal rails and side panels

	α^{90° can be combined	α^{90° combination not recommended	
Alu-pan	-	aluminum 303 stainless steel aluminum 6063-T5 powder coated	aluminum 303 stainless steel
Alu-pan 2	+	aluminum 303 stainless steel aluminum 6063-T5 powder coated	aluminum 303 stainless steel
Alu-pan 3	+	aluminum 303 stainless steel	-
Alu-pan 4	-	-	-
Alu-pan 5	-	-	-
Alu-pan 6	-	-	-
Alu-pan 7	-	-	-
Alu-pan 8	-	-	-
Alu-pan 9	-	-	-
Alu-pan 10	-	-	-
Alu-pan 11	-	-	-
Alu-pan 12	-	-	-
Alu-pan 13	-	-	-
Alu-pan 14	-	-	-
Alu-pan 15	-	-	-
Alu-pan 16	-	-	-
Alu-pan 17	-	-	-
Alu-pan 18	-	-	-
Alu-pan 19	-	-	-
Alu-pan 20	-	-	-
Alu-pan 21	-	-	-
Alu-pan 22	-	-	-
Alu-pan 23	-	-	-
Alu-pan 24	-	-	-
Alu-pan 25	-	-	-
Alu-pan 26	-	-	-
Alu-pan 27	-	-	-
Alu-pan 28	-	-	-
Alu-pan 29	-	-	-
Alu-pan 30	-	-	-
Alu-pan 31	-	-	-
Alu-pan 32	-	-	-
Alu-pan 33	-	-	-
Alu-pan 34	-	-	-
Alu-pan 35	-	-	-
Alu-pan 36	-	-	-
Alu-pan 37	-	-	-
Alu-pan 38	-	-	-
Alu-pan 39	-	-	-
Alu-pan 40	-	-	-
Alu-pan 41	-	-	-
Alu-pan 42	-	-	-
Alu-pan 43	-	-	-
Alu-pan 44	-	-	-
Alu-pan 45	-	-	-
Alu-pan 46	-	-	-
Alu-pan 47	-	-	-
Alu-pan 48	-	-	-
Alu-pan 49	-	-	-
Alu-pan 50	-	-	-
Alu-pan 51	-	-	-
Alu-pan 52	-	-	-
Alu-pan 53	-	-	-
Alu-pan 54	-	-	-
Alu-pan 55	-	-	-
Alu-pan 56	-	-	-
Alu-pan 57	-	-	-
Alu-pan 58	-	-	-
Alu-pan 59	-	-	-
Alu-pan 60	-	-	-
Alu-pan 61	-	-	-
Alu-pan 62	-	-	-
Alu-pan 63	-	-	-
Alu-pan 64	-	-	-
Alu-pan 65	-	-	-
Alu-pan 66	-	-	-
Alu-pan 67	-	-	-
Alu-pan 68	-	-	-
Alu-pan 69	-	-	-
Alu-pan 70	-	-	-
Alu-pan 71	-	-	-
Alu-pan 72	-	-	-
Alu-pan 73	-	-	-
Alu-pan 74	-	-	-
Alu-pan 75	-	-	-
Alu-pan 76	-	-	-
Alu-pan 77	-	-	-
Alu-pan 78	-	-	-
Alu-pan 79	-	-	-
Alu-pan 80	-	-	-
Alu-pan 81	-	-	-
Alu-pan 82	-	-	-
Alu-pan 83	-	-	-
Alu-pan 84	-	-	-
Alu-pan 85	-	-	-
Alu-pan 86	-	-	-
Alu-pan 87	-	-	-
Alu-pan 88	-	-	-
Alu-pan 89	-	-	-
Alu-pan 90	-	-	-
Alu-pan 91	-	-	-
Alu-pan 92	-	-	-
Alu-pan 93	-	-	-
Alu-pan 94	-	-	-
Alu-pan 95	-	-	-
Alu-pan 96	-	-	-
Alu-pan 97	-	-	-
Alu-pan 98	-	-	-
Alu-pan 99	-	-	-
Alu-pan 100	-	-	-

34566-320

The rugged horizontal rail type can handle shock and vibration up to 25 g. It enables the use of IEEE handles.

Type R-LD "rugged" horizontal rails with 3-hole fixing for increased robustness

For insertion/extraction of CompactPCI or, VME64x boards

With HP units printed from 28 HP upwards

Length 20, 28, 40, 42, 63, 84 HP or 1000 mm

Aluminum extrusion, anodized finish, conductive contact surface, with HP markings



PRODUCT ATTRIBUTES

Rack Width: 20HP

Package Quantity: 1

Finish: Anodized

Length: 106.68mm

Material: Aluminum

Product Family: EuropacPRO

Product Type: Horizontal Rail

Type: Rugged, LD

Works With: Subracks

Net Weight: 0.03kg

*The price shown is the per piece price and does not include VAT. Depending on local conditions, packaging and freight charges might not be included. Where these charges should be part of the total price, they are included in the quote. The price given is a non-binding recommended retail price (RRP), which is the nVent list price. The final sales prices of local distributors may vary. Quotations requested or generated on SCHROFF.nVent.com are only valid for commercial customers (B2B). The lead time displayed above is an estimate for this item to be dispatched from an nVent Schroff facility. Transit delivery times are not included in this estimate, as transit time may vary, depending on delivery address, parcel dimensions, and other factors. Cut-outs and modifications placed in non-recommended areas ("collision detected") for configured products may be subject to additional engineering and/or design costs, which may increase initially quoted prices.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff

