

nVent CADDY Pyramid Tool-Free Cable Tray Support Kit



FEATURES

Push-in pins install without the need for additional tools

Plastic pins and base will not corrode

Pins and mounting holes accommodate most perforated cable tray

Ready to use out of the box, saving installation time and labor

Additional pins can be purchased separately

Foam bottom offers low abrasion interface for better roof membrane protection

Provides superior load distribution, even with varying rooftop surfaces

Compatible with roof surfaces including single ply, bituminous, metal and spray foam

Multiple sizes and load ratings offer the ability to tailor the solution to the application

Easy to transport to the roof

Material: Polyethylene;Polypropylene;Nylon
Temperature: -45 to 65 °C
Static Load Safety Factor: 3:1

SPECIFICATIONS

Table 1/2

Catalog Number	Article Number	E-Number	Length (L)	Width (W)	Height (H)	Surface Area
PTF10P	360519	1319821	318mm	201 mm	102 mm	59355mm ²
PTF16P	360522	1319823	480mm	201 mm	102 mm	91613mm ²
PTF6P	360518	1319820	196mm	150 mm	102 mm	26452mm ²

Table 2/2

Catalog Number	Article Number	E-Number	Unit Weight	Static Load
PTF10P	360519	1319821	0.5 kg	4450N

Catalog Number	Article Number	E-Number	Unit Weight	Static Load
PTF16P	360522	1319823	1 kg	6670N
PTF6P	360518	1319820	0.3 kg	1330N

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
 Option 1 – Customer Care
 Option 2 – Technical Support

Europe

Netherlands:
 +31 800-0200135
 France:
 +33 800 901 793

Europe

Germany:
 800 1890272
 Other Countries:
 +31 13 5835404

APAC

Shanghai:
 + 86 21 2412 1618/19
 Sydney:
 +61 2 9751 8500

