


Double Protection Cables Entry For Wall Mounted Enclosures, CED



The rubber cable gland is easy to mount, and, cables and pipes can be pulled through easily without tools, ensuring that the enclosure's protection degree is maintained.

FEATURES

Description: The rubber grommet is very simple to use. The installation does not require tools, which in turn means lower work cost. The "pushout" membrane is a permanent seal until it is penetrated by a cable or pipe. Suitable for holes in materials of 0.5 to 4 mm thickness.

Material: EPDM, halogen free.

Temperature resistance: -40 °C to +110 °C.

Finish: RAL 7035.

Protection: IP 67.

The protection degree is maintained if the outside layer fails due to damage or external circumstances

The double layer sock is the optimal solution if the outside layer is exposed to external circumstances such as high pressure water

A potential disadvantage of the double layer however is that cables only pass through straight

A single layer sock is available (CES) to allow cable passing through with an angle but the protection degree might be at risk if this single layer fails


Material: EPDM
Finish: Smooth
Color: Light Gray
Color Code: RAL 7035

SPECIFICATIONS

Catalog Number	E-Number	Height (H)	Width (W)	Depth (D)	Height 1 (H1)	Diameter
CED12	2411060	20mm	20mm	12.8mm	5.6mm	20mm
CED16	2411061	21mm	21mm	17.7mm	11mm	21mm

Catalog Number	E-Number	Height (H)	Width (W)	Depth (D)	Height 1 (H1)	Diameter
CED20	2411062	25.5mm	25.5mm	20mm	13.4mm	25.5mm
CED25	2411063	30.5mm	30.5mm	21.3mm	15.3mm	30.5mm
CED32	2411064	38.5mm	38.5mm	24.6mm	18.6mm	38.5mm
CED40	2411065	48.5mm	48.5mm	29.5mm	21.7mm	48.5mm
CED50	2411066	60.5mm	60.5mm	34.8mm	25mm	60.5mm

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

