


# Signal Reference Grid



## FEATURES

Provides a low impedance equipotential plane to protect sensitive electronic equipment from transient noise

Pre-engineered welded grid of 26 gauge copper strips reduces voltage differences between interconnected electronic equipment

Welded connections do not deteriorate, corrode or loosen with time

Can be easily field-welded to suit any size computer room

Complies with IEEE® Standard 1100-1992

**Material:** Copper




## SPECIFICATIONS

| Catalog Number | Article Number | Length 1 (L1) | Width 1 (W1) | Grid Spacing (L2 x W2) | Thickness (T) | Strip Width |
|----------------|----------------|---------------|--------------|------------------------|---------------|-------------|
| SRGBD100       | 167901         | 30500 mm      | 3.05 m       | 609.6 mm x 609.6 mm    | 0.4 mm        | 50.4mm      |
| SRGBE100       | 167902         | 30480 mm      | 3.66 m       | 609.6 mm x 609.6 mm    | 0.4 mm        | 50.4mm      |

## ADDITIONAL PRODUCT DETAILS

Custom sizes available upon request. Contact your nVent ERICO representative for more information.



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical  
Support

Europe

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

Europe

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY   ERICO   HOFFMAN   ILSCO   SCHROFF   TRACHTE