

Hazardous Location Window Kits



Hazardous Location Window Kits are designed to be used on Increased Safety (Ex e) enclosures in ATEX or IECEx Zone 1 or 2 hazardous areas. These window kits ensure a dust-, oil-, and water-tight seal. Designed for use as viewing windows, these window kits are ideal for visibility of internal enclosure components. The windows are easily installed by making a cutout in the enclosure and attaching the window and frame with included mounting hardware.

INDUSTRY STANDARDS

UL 508A Component Recognized; Type 4, 4X, 12, 3R; File No. E61997

IECEx and ATEX Approvals

Suitable for use on increased safety enclosures for ZONE 1 or ZONE 2 assemblies

ATEX Directive 94/9/EC

ATEX

Sira 13ATEX3315U

Ex e IIC Gb

Ex tb IIIC Db IP 66

IECEx

IECEx SIR 13.0123U

Ex e IIC Gb

Ex tb IIIC Db IP 66

cUR Component Recognized per CSA C22.2 No. 94; Type 4, 4X, 12,

3R; File No. E61997

NEMA/EEMAC 4, 4X, 12, 13

IEC 60529, IP66

FEATURES

Secure sealing with silicon gasket to protect against water and dust ingress in high-temperature applications

Maintain visual on components through .25-in. (6-mm) tempered safety glass

Easy installation in enclosure cutouts with window frame hardware

Material: Stainless Steel 316L

SPECIFICATIONS

Catalog Number	Article Number	Thickness	Cutout Size
EXWK715SS6	27025	14ga	16.69 x 8.69in
EXWK53SS6	27021	14ga	6.69 x 4.69in
EXWK711SS6	27023	14ga	8.69 x 12.69in
EXWK95SS6	27022	14ga	10.69 x 7.19in
EXWK720SS6	27027	14ga	8.69 x 21.69in
EXWK1711SS6	27026	14ga	18.69 x 12.69in
EXWK138SS6	27024	14ga	14.69 x 9.69in
EXWK2919SS6	27033	14ga	30.69 x 20.69in
EXWK724SS6	27031	14ga	8.69 x 25.69in
EXWK2315SS6	27028	14ga	24.69 x 16.69in
EXWK729SS6	27032	14ga	8.69 x 30.69in

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE