



	"B" can be combined.		"A" combination not recommended		
Stange 2.0		-	+	+	Stange 3.0 ragged
Stange 3.0		+	Stange 3.0 flexible (for Expansion)	Stange 3.0 flexible (for safety anchoring)	+
Stange 3.5		Stange 3.5 light	Stange 3.5 flexible	-	-
Stange 4.0		Stange 4.0 light	Stange 4.0 flexible	-	-
Stange 4.5		Stange 4.5 light	Stange 4.5 flexible	-	-
Stange 5.0		Stange 5.0 light	Stange 5.0 flexible	-	-
Stange 6.0		Stange 6.0 light	Stange 6.0 flexible	-	-
Stange 7.0		Stange 7.0 light	Stange 7.0 flexible	-	-
Stange 8.0		Stange 8.0 light	Stange 8.0 flexible	-	-
Stange 9.0		Stange 9.0 light	Stange 9.0 flexible	-	-
Stange 10.0		Stange 10.0 light	Stange 10.0 flexible	-	-
Stange 11.0		Stange 11.0 light	Stange 11.0 flexible	-	-
Stange 12.0		Stange 12.0 light	Stange 12.0 flexible	-	-
Stange 13.0		Stange 13.0 light	Stange 13.0 flexible	-	-
Stange 14.0		Stange 14.0 light	Stange 14.0 flexible	-	-
Stange 15.0		Stange 15.0 light	Stange 15.0 flexible	-	-
Stange 16.0		Stange 16.0 light	Stange 16.0 flexible	-	-
Stange 17.0		Stange 17.0 light	Stange 17.0 flexible	-	-
Stange 18.0		Stange 18.0 light	Stange 18.0 flexible	-	-
Stange 19.0		Stange 19.0 light	Stange 19.0 flexible	-	-
Stange 20.0		Stange 20.0 light	Stange 20.0 flexible	-	-
Stange 21.0		Stange 21.0 light	Stange 21.0 flexible	-	-
Stange 22.0		Stange 22.0 light	Stange 22.0 flexible	-	-
Stange 23.0		Stange 23.0 light	Stange 23.0 flexible	-	-
Stange 24.0		Stange 24.0 light	Stange 24.0 flexible	-	-
Stange 25.0		Stange 25.0 light	Stange 25.0 flexible	-	-
Stange 26.0		Stange 26.0 light	Stange 26.0 flexible	-	-
Stange 27.0		Stange 27.0 light	Stange 27.0 flexible	-	-
Stange 28.0		Stange 28.0 light	Stange 28.0 flexible	-	-
Stange 29.0		Stange 29.0 light	Stange 29.0 flexible	-	-
Stange 30.0		Stange 30.0 light	Stange 30.0 flexible	-	-
Stange 31.0		Stange 31.0 light	Stange 31.0 flexible	-	-
Stange 32.0		Stange 32.0 light	Stange 32.0 flexible	-	-
Stange 33.0		Stange 33.0 light	Stange 33.0 flexible	-	-
Stange 34.0		Stange 34.0 light	Stange 34.0 flexible	-	-
Stange 35.0		Stange 35.0 light	Stange 35.0 flexible	-	-
Stange 36.0		Stange 36.0 light	Stange 36.0 flexible	-	-
Stange 37.0		Stange 37.0 light	Stange 37.0 flexible	-	-
Stange 38.0		Stange 38.0 light	Stange 38.0 flexible	-	-
Stange 39.0		Stange 39.0 light	Stange 39.0 flexible	-	-
Stange 40.0		Stange 40.0 light	Stange 40.0 flexible	-	-
Stange 41.0					

34560-528

CARACTERÍSTICAS

< 28 HP no impreso

Extrusión de aluminio, acabado anodizado, superficie de contacto conductora, con marcas HP

Peso neto: 0.046kg

nVent.com/SCHROFF | 1

DETALLES ADICIONALES DEL PRODUCTO

La entrega es en paquete estándar múltiplos. El precio es por artículo individual.

ADVERTENCIA

Los productos nVent deben instalarse y usarse solo como se indica en las hojas de instrucciones y materiales de capacitación del producto nVent. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. La instalación incorrecta, el mal uso, la aplicación incorrecta u otras fallas en el seguimiento completo de las instrucciones y advertencias de nVent pueden causar el mal funcionamiento del producto, daños a la propiedad, lesiones corporales graves y la muerte y/o anular la garantía.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff

